

View Online at <https://aerobasegroup.com/nsn/5935-00-630-5223>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

2.625 inches

**Overall Height:**

0.755 inches

**Overall Width:**

Between 0.333 inches and 0.353 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.119 inches

**Distance Between Mounting Facility Centers:**

Between 2.148 inches and 2.164 inches

**Board Accommodated Length:**

1.718 inches single board and 1.730 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Fixed inter-contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class @1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

10 single mating end single contact grouping

**Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-21097/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.