NSN 5935-00-630-6034

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-630-6034

2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.900 inches
Overall Height:
0.672 inches
Overall Width:
0.360 inches
Distance Between Mounting Facility Centers:
2.600 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
23 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.218 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping

NSN 5935-00-630-6034

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, type sdi-5 military specification single material response single mating end

Included Contact Quantity:

23 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.023 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.