Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-630-7476

Thread Class:
2g
Thread Pitch Diameters:
+0.113/+0.125 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.703 inches
Overall Height:
Between 2.219 inches and 2.250 inches
Overall Width:
Between 2.219 inches and 2.250 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.682 inches and 1.692 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.682 inches and 1.692 inches
Distance From Mounting Shoulder To Front Face:
Between 1.000 inches and 1.010 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
A single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
105.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
4

NSN 5935-00-630-7476

Electrical Receptacle Connector - Page 2 of 2



Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Material Specification:

Qq-a-270, t6 military specification single material response

Insert Material Specification:

Mil-r-3065 military specification single material response single mating end

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy and 0.020 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.