## NSN 5935-00-631-5759

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-631-5759 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.180 inches **Overall Height:** 1.297 inches **Overall Width:** 1.297 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.986 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.986 inches **Distance From Mounting Shoulder To Front Face:** Between 0.580 inches and 0.608 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 27-50 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Spring friction Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.062 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-631-5759

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Nickel
Shell Material Specification:
Qq-a-367, t6 federal specification single material response
Included Contact Quantity:
27 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.027 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039b0