NSN 5935-00-632-6468

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-632-6468

Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.234 inches
Overall Diameter:
1.281 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
34.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:

Precious Material:

Precious Material And Weight:

Contact surfaces gold and contact surfaces silver

0.037 gold grains, troy and 0.037 silver grains, troy

Gold and silver

NSN 5935-00-632-6468

Electrical Plug Connector - Page 2 of 2



Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specifi	cation	Data:
---------	--------	-------

81349-mil-c-38999	government	specification
-------------------	------------	---------------

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.