Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-632-7437

#### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

0.697 inches

## **Overall Height:**

1.328 inches

#### **Overall Width:**

1.328 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

#### 0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

# 1.062 inches

Distance From Mounting Shoulder To Front Face:

#### 0.447 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-66 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

342.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy



# **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 66 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.066 gold grains, troy and 0.066 silver grains, troy **Precious Material:** Gold and silver **Test Data Document:** 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 96906-ms27508 government standard Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-c-38999 spec.

---