

View Online at <https://aerobasegroup.com/nsn/5935-00-633-5056>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, external coupling

**Overall Length:**

1.000 inches

**Overall Height:**

1.359 inches

**Overall Diameter:**

0.625 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Cable Entrance Diameter:**

Between 0.258 inches and 0.261 inches

**Distance From Mounting Shoulder To Front Face:**

0.734 inches

**Mounting Facility Thickness:**

0.190 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic fluorinated ethylene propylene single mating end or plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0