NSN 5935-00-633-7071

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-633-7071

| Thread Direction: |
|---|
| Right-hand |
| Overall Length: |
| 1.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.375 inches |
| Overall Height: |
| 1.406 inches |
| Overall Width: |
| 1.750 inches |
| Environmental Protection: |
| Pressure proof and corrosion resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.147 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.375 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Maximum Current Rating In Amps: |
| 20.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 150.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 200.0 single mating end single contact grouping |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 1.500 inches |
| Insert Material: |
| Plastic single mating end |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 2 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Polarized; 4 mtg holes; dim. Excl protruding terminals |
| Thread Series Designator: |

Unef

NSN 5935-00-633-7071

Electrical Receptacle Connector - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0