

View Online at <https://aerobasegroup.com/nsn/5935-00-636-5806>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.094 inches

**Overall Diameter:**

0.595 inches

**Environmental Protection:**

Corrosion resistant and shock proof and vibration proof

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sm 1st mating end

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin and externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

32 and 32

**Thread Size:**

0.250 inches and 0.375 inches

**Contact Surface Treatment:**

Silver all mating ends single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Special Features:**

Complete sm non-weatherproof plugs used internally to type bnc weatherproof plugs used externally

**Precious Material And Location:**

Body surfaces silver and contact surfaces silver

**Precious Material And Weight:**

0.110 silver grains, troy

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-a-27434 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef

**Specification Data:**

81349-mil-a-27434/21 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0