

View Online at <https://aerobasegroup.com/nsn/5935-00-636-5806>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.094 inches

Overall Diameter:

0.595 inches

Environmental Protection:

Corrosion resistant and shock proof and vibration proof

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Sm 1st mating end

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.250 inches and 0.375 inches

Contact Surface Treatment:

Silver all mating ends single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Special Features:

Complete sm non-weatherproof plugs used internally to type bnc weatherproof plugs used externally

Precious Material And Location:

Body surfaces silver and contact surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Test Data Document:

81349-mil-a-27434 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-a-27434/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0