NSN 5935-00-639-1382

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-639-1382 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape **Overall Length:** 2.719 inches **Overall Height:** 1.125 inches **Overall Width:** 0.781 inches **Distance Between Mounting Facility Centers:** 2.140 inches **Threaded Device Type:** Mounting stud and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Jackscrew Thread Length: 0.375 inches Thready Qty Per Inch (tpi): 32 and 32 **Thread Size:** 0.138 inches and 0.164 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic melamine single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-639-1382

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.012 gold grains, troy and 0.012 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0