NSN 5935-00-642-0992

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-642-0992 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.188 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility and hub **Mating End Quantity: Contact Position Arrangement Style:** 20-20 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Detent

NSN 5935-00-642-0992

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.188 inches and 1.1250 inches
Terminal Location:
Back single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Included Contact Quantity:
3 single mating end 2nd contact grouping
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A039b0