NSN 5935-00-642-4053

Thread Class:

Thread Direction:

2a

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-642-4053



Right-hand **Body Style:** Straight shape **Overall Length:** 1.219 inches **Overall Height:** 0.781 inches **Overall Width:** 0.375 inches **Environmental Protection:** Pressure proof and moisture resistant and salt water resistant and vibration resistant **Distance Between Mounting Facility Centers:** 0.906 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping

NSN 5935-00-642-4053

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.007 gold grains, troy and 0.007 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0