## NSN 5935-00-643-6719

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-643-6719 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Unthreaded Mounting Hole Diameter:** 0.173 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 36-8 single mating end **Contact Removability:** Removable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-00-643-6719

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
16
Thread Size:
2.250 inches
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
46 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0