## NSN 5935-00-643-7738

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-643-7738 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 6.562 inches **Overall Diameter:** 5.000 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 25.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 120.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.563 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** 

Included Contact Quantity:

2 single mating end single contact grouping

Solder well single mating end single contact grouping

## NSN 5935-00-643-7738

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Solder flange mtg
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0