

View Online at <https://aerobasegroup.com/nsn/5935-00-644-5121>

Body Style:

Straight shape

Overall Length:

1.875 inches

Overall Height:

0.938 inches

Overall Width:

1.250 inches

Unthreaded Mounting Hole Diameter:

Between 0.126 inches and 0.134 inches

Distance Between Mounting Facility Centers:

1.500 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

150.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end 2nd contact grouping

Polarization Method:

Contact

Shell Type:

Solid

End Application:

Boliers, 1200 psi; integrated launch & recovery tv surveillance sys (ilarts); virginia class cgn (41); spruance class dd (963); forrestal class cv; mk 38 gun fire control system; ticonderoga class cg (47); helicopter, advance attack, ah-1w

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Rubber single mating end

Criticality Code Justification:

Feat

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Iron

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end all contact groupings

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0