

View Online at <https://aerobasegroup.com/nsn/5935-00-644-5121>

**Body Style:**

Straight shape

**Overall Length:**

1.875 inches

**Overall Height:**

0.938 inches

**Overall Width:**

1.250 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.126 inches and 0.134 inches

**Distance Between Mounting Facility Centers:**

1.500 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

150.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end 2nd contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**End Application:**

Boliers, 1200 psi; integrated launch & recovery tv surveillance sys (ilarts); virginia class cgn (41); spruance class dd (963); forrestal class cv; mk 38 gun fire control system; ticonderoga class cg (47); helicopter, advance attack, ah-1w

**Terminal Location:**

Back single mating end all contact groupings

**Insert Material:**

Rubber single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw single mating end all contact groupings

**Shell Material:**

Iron

**Included Contact Quantity:**

1 single mating end 2nd contact grouping

**Included Contact Type:**

Flat socket single mating end all contact groupings

**Special Features:**

Weapon system essential

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0