

View Online at <https://aerobasegroup.com/nsn/5935-00-644-6486>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.703 inches and 0.797 inches

Overall Height:

Between 1.234 inches and 1.266 inches

Overall Width:

Between 1.234 inches and 1.266 inches

Unthreaded Mounting Hole Diameter:

Between 0.164 inches and 0.174 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.967 inches and 0.977 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.967 inches and 0.977 inches

Distance From Mounting Shoulder To Front Face:

Between 0.422 inches and 0.453 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Gk-c8 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

16.0 single mating end 2nd contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

6

Thread Size:

1.187 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

5 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.008 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0