

View Online at <https://aerobasegroup.com/nsn/5935-00-644-7033>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.000 inches

Overall Height:

0.843 inches

Overall Width:

0.438 inches

Distance Between Mounting Facility Centers:

0.688 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

6 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and silver single mating end single contact grouping

Insert Material:

Plastic melamine mineral filled single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-746, grade a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-14, ty mfe military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right hand and jackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.006 gold grains, troy and 0.006 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-14 spec.