

View Online at <https://aerobasegroup.com/nsn/5935-00-644-7196>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 0.703 inches and 0.797 inches

**Overall Height:**

Between 1.609 inches and 1.641 inches

**Overall Width:**

Between 1.609 inches and 1.641 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.149 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.254 inches and 1.264 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.254 inches and 1.264 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.422 inches and 0.453 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nk-27 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Thready Qty Per Inch (tpi):**

6

**Thread Size:**

1.563 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

27 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.027 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0