

View Online at <https://aerobasegroup.com/nsn/5935-00-644-9296>

Body Style:

Hood, side opening, w/clamp

Overall Length:

2.609 inches

Overall Height:

1.719 inches

Overall Width:

1.062 inches

Cable Entrance Diameter:

Between 0.219 inches and 0.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Shell Type:

Hood, side opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.016 gold grains, troy and 0.016 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.