Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-646-6512

Thread	Class:

2a

**Thread Direction:** 

Right-hand

## **Body Style:**

Locking plug/socket type

#### **Overall Height:**

6.188 inches

#### **Overall Diameter:**

2.688 inches

## **Environmental Protection:**

Moisture resistant

#### **Threaded Device Type:**

Back shell

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-10 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

30.0 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

315.0

Shell Type:

Solid

# **Connector Locking Method:**

Friction

# Connector Cable Strain Relief Method:

Cable clamp

# Thready Qty Per Inch (tpi):

12

## Thread Size:

1.500 inches

### **Terminal Location:**

Back single mating end single contact grouping

# NSN 5935-00-646-6512

Electrical Plug Connector - Page 2 of 2



**Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Anodize **Included Contact Quantity:** 4 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0