NSN 5935-00-646-6519

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-646-6519

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.099 inches and 1.119 inches

Overall Height:

Between 1.677 inches and 1.697 inches

Overall Width:

Between 3.365 inches and 3.385 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.870 inches and 2.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.052 inches and 0.072 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

G20 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

40.0 single mating end 2nd contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings and gold single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

8 single mating end 2nd contact grouping

NSN 5935-00-646-6519

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces silver and contact surfaces gold

Precious Material And Weight:

0.020 silver grains, troy and 0.020 gold grains, troy

Precious Material:

Silver and gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0