NSN 5935-00-646-6521

Body Style:Straight shape

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-646-6521

| Overall Length: |
|--|
| 0.688 inches |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.093 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 0.495 inches and 0.505 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 1.775 inches and 1.785 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.468 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 24c2 single mating end |
| Contact Removability: |
| Removable single mating end 1st contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end 2nd contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end all contact groupings |
| Terminal Type: |
| Solder well single mating end 2nd contact grouping |
| |

NSN 5935-00-646-6521

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|---|
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 22 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round socket single mating end 2nd contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.024 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |