

View Online at https://aerobasegroup.com/nsn/5935-00-646-8000

Thread Olares	
Thread Class:	
2a and 2a	
Thread Direction:	
Right-hand and right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
1.094 inches	
Overall Height:	
Between 1.168 inches and 1.208 inches	
Overall Width:	
Between 1.168 inches and 1.208 inches	
Environmental Protection:	
Explosion proof and salt water resistant	
Unthreaded Mounting Hole Diameter:	
Between 0.148 inches and 0.154 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 0.901 inches and 0.911 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 0.901 inches and 0.911 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.562 inches and 0.578 inches	
Threaded Device Type:	
Back shell and coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
14s-7 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
22.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	
Thready Qty Per Inch (tpi):	
20 and 10	

## NSN 5935-00-646-8000

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.750 inches and 0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.003 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0