# NSN 5935-00-647-3519



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-647-3519 **Body Style:** Straight shape, external coupling **Overall Length:** 1.137 inches **Overall Height:** 0.812 inches **Overall Width:** 0.812 inches **Environmental Protection:** Humidity resistant and dripproof and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Distance From Mounting Shoulder To Front Face:** 0.431 inches **Mating End Quantity: Contact Position Arrangement Style:** 8-4 single mating end **Contact Removability:** 

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### **Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

#### **Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

#### **Shell Type:**

Solid

#### **Connector Locking Method:**

Bayonet pin

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# NSN 5935-00-647-3519

A039b0

Mil-p-3065 spec.

Mil-std (military Standard):

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-p-3065, type s, class sc, grade 715a1b1e3 military specification single material response single mating end
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.004 gold grains, troy and 0.004 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: