NSN 5935-00-649-7055

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-649-7055

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Angle shape, external/internal coupling
Overall Length:
1.456 inches
Overall Height:
1.598 inches
Overall Width:
0.875 inches
Environmental Protection:
Corrosion resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Hn all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell and internally threaded coupling ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi):
20
Thread Size:
0.750 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Plastic polytetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Qq-s-561 federal specification single treatment response all mating ends single contact grouping
Shell Material:
Copper alloy

NSN 5935-00-649-7055

Connector Adapter - Page 2 of 2



Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-561 federal specification single treatment response
Shell Material Specification:
Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response
Insert Material Specification:
Mil-m-14077 military specification single material response all mating ends
Included Contact Quantity:
1 2nd mating end single contact grouping
Included Contact Type:
Coaxial socket 1st mating end single contact grouping
Precious Material And Location:
Contact and body surfaces silver
Precious Material And Weight:
0.110 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14077 spec.