

NSN 5935-00-650-9985 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-650-9985 **Body Style:** Straight shape **Overall Length:** 1.480 inches **Overall Height:** 0.365 inches **Overall Width:** 0.208 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.089 inches and 0.094 inches **Distance Between Mounting Facility Centers:** 1.270 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy a380.0

Shell Surface Treatment:

Nickel

Shell Material Specification:

Qq-a-591, alloy a380 federal specification single material response

NSN 5935-00-650-9985

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-19833, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.