NSN 5935-00-655-1243

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-1243

Body Style:
T-shape
Overall Length:
1.031 inches
Overall Height:
0.320 inches
Overall Width:
0.750 inches
Environmental Protection:
Corrosion resistant and salt water resistant
Mating End Quantity:
3
Contact Position Arrangement Style:
Mb all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 all mating ends all contact groupings
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver Included Contact Quantity:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver Included Contact Quantity: 1 2nd mating end all contact groupings
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Silver all mating ends all contact groupings Insert Material: Plastic tetrafluoroethylene all mating ends Shell Material: Copper alloy Shell Surface Treatment: Silver Included Contact Quantity: 1 2nd mating end all contact groupings Included Contact Type:

0.115 silver grains, troy

Precious Material And Weight:

NSN 5935-00-655-1243

Connector Adapter - Page 2 of 2



Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Fiig:

No

A039b0