## NSN 5935-00-655-1244

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-1244 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.609 inches **Overall Diameter:** 0.344 inches **Environmental Protection:** Corrosion resistant **Cable Entrance Diameter:** 0.086 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

## NSN 5935-00-655-1244

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces and shell surfaces silver
Precious Material And Weight:
0.105 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0