NSN 5935-00-655-1774

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-1774

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.404 inches

Overall Height:

0.864 inches

Overall Width:

0.343 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.142 inches

Distance Between Mounting Facility Centers:

2.156 inches

Board Accommodated Length:

1.723 inches single board

Board Accommodated Width:

0.082 inches

Mating End Quantity:

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

NSN 5935-00-655-1774

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location: Contact surface gold and contact surface silver Precious Material And Weight: 0.010 gold grains, troy and 0.010 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

Mil-std (military Standard): Mil-m-14 spec.

A039b0