Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-3494

# Thread Class:

2g

**Thread Direction:** 

Right-hand

#### **Body Style:**

Angle shape w/cable clamp

# **Overall Diameter:**

1.520 inches

#### Body Angle In Deg:

45.0

#### Cable Entrance Diameter:

0.656 inches

#### **Threaded Device Type:**

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

"50, 21-50" single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

80.0

#### Shell Type:

Solid

#### Connector Locking Method:

Internally threaded coupling ring

#### **Connector Cable Strain Relief Method:**

Cable clamp

# Thready Qty Per Inch (tpi):

6

#### Thread Size:

1.312 inches

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# NSN 5935-00-655-3494

Electrical Plug Connector - Page 2 of 2



**Insert Material:** Plastic melamine single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 50 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.050 gold grains, troy and 0.050 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Acme Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0