## NSN 5935-00-655-4168

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-4168

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 0.584 inches and 0.604 inches

**Overall Diameter:** 

0.234 inches

**Environmental Protection:** 

Moisture resistant

**Distance From Mounting Shoulder To Front Face:** 

0.421 inches

**Mounting Facility Thickness:** 

0.094 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32 and 32

**Thread Size:** 

0.190 inches and 0.190 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

## NSN 5935-00-655-4168

Electrical Receptacle Connector - Page 2 of 2



| Insert Material:                                      |
|---|
| Plastic tetrafluoroethylene single mating end         |
| Terminal Type:  |
| Solder well single mating end single contact grouping |
| Shell Material:                                       |
| Copper alloy  |
| Shell Surface Treatment:                              |
| Gold and copper                                       |
| Included Contact Quantity:                            |
| 1 single mating end single contact grouping           |
| <b>Bushing Accommodation Hole Shape:</b>              |
| Round   |
| Included Contact Type:                                |
| Coaxial pin single mating end single contact grouping |
| Precious Material And Location:                       |
| Contact and shell surfaces gold                       |
| Precious Material And Weight:                         |
| 0.105 gold grains, troy                               |
| Precious Material:                                    |
| Gold  |
| Thread Series Designator:                             |
| Unf and unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |
| No  |
| Fiig:   |
| A039b0  |
|   |