## NSN 5935-00-655-4414

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-655-4414

**Body Style:** 

Straight shape, rectangular

**Overall Length:** 

Between 3.177 inches and 3.197 inches

**Overall Height:** 

0.656 inches

Overall Width:

Between 0.318 inches and 0.338 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.100 inches and 0.140 inches

**Distance Between Mounting Facility Centers:** 

Between 2.927 inches and 2.947 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Included Contact Quantity:** 

34 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-655-4414

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:	
0.034 gold grains, troy and 0.034 silver grains, troy	
Precious Material:	
Gold and silver	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	

Mil-std (military Standard):

Mil-g-45204 spec.