NSN 5935-00-655-4427



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-655-4427 **Thread Class:** 2a **Thread Pitch Diameters:** +1.312/+1.321 inches **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.733 inches **Overall Height:** 1.531 inches **Overall Width:** 1.531 inches **Unthreaded Mounting Hole Diameter:** 0.171 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.406 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** "50, 21-50" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 280.0 Shell Type: Solid **Connector Locking Method:**

6

Externally threaded shell Thready Qty Per Inch (tpi):

NSN 5935-00-655-4427

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-14, ty mme military specification single material response single mating end
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.