## NSN 5935-00-660-5070



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-660-5070 **Thread Direction:** Right-hand **Overall Length:** 2.000 inches **Overall Height:** 1.899 inches **Overall Width:** 2.000 inches **Environmental Protection:** Humidity resistant and shock proof **Unthreaded Mounting Hole Diameter:** 0.177 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.750 inches **Insert Material:** Plastic single mating end **Shell Material:** Aluminum alloy **Included Contact Quantity:** 4 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end all contact groupings

Special Features:

Polarized; 4 mtg holes

## NSN 5935-00-660-5070

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0