NSN 5935-00-660-5205

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-660-5205

Body Style:
Straight shape, rectangular
Overall Length:
1.620 inches
Overall Height:
0.920 inches
Overall Width:
0.750 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.152 inches
Distance Between Mounting Facility Centers:
1.250 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Chall Turner
Shell Type:
Solid Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Friction
Solid Connector Locking Method: Friction Terminal Location:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type:
Solid Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping Terminal Type: Solder well single mating end single contact grouping Included Contact Quantity:

Contact surfaces gold

Precious Material And Location:

NSN 5935-00-660-5205

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.