

View Online at <https://aerobasegroup.com/nsn/5935-00-660-5790>

Body Style:

Hood, top opening w/clamp

Overall Length:

1.495 inches

Overall Height:

1.688 inches

Overall Width:

0.610 inches

Cable Entrance Diameter:

0.422 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Hood, top opening

Connector Locking Method:

Latch

Connector Cable Strain Relief Method:

Cable clamp

End Application:

Tleltype model 28. Mx peacekeeper missile support equipment. An/tsc-86 satellite communications terminal. B-1 aircraft support equipment. Sturgeon classssn (637). All-weather anti-ship harpoon (agm-84) missile. Hh-60h and hh-60j search and rescue helicopters. Torpedo systems mk-46. Sh-60f carrier based helicopter

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Criticality Code Justification:

Feat

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Insert Material Specification:

Mil-m-14, @type mdg military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.014 gold grains, troy and 0.014 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.