

View Online at <https://aerobasegroup.com/nsn/5935-00-660-5851>

Body Style:

Straight shape w/flange

Overall Length:

1.125 inches

Overall Height:

1.454 inches

Overall Width:

1.454 inches

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.120 inches and 1.130 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.120 inches and 1.130 inches

Distance From Mounting Shoulder To Front Face:

Between 0.562 inches and 0.593 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

16-26 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

7.5 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 all mating ends single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-f-14072, finish e516 military specification single treatment response

Insert Material Specification:

Mil-r-3065 military specification single material response all mating ends

Included Contact Quantity:

26 1st mating end single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.052 gold grains, troy and 0.052 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.