NSN 5935-00-660-5914

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-660-5914 **Body Style:** Straight shape threaded **Overall Length:** 1.125 inches **Overall Diameter:** 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.656 inches **Mounting Facility Thickness:** 0.094 inches **Mating End Quantity: Contact Position Arrangement Style:** 12-p single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:**

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

12 single mating end single contact grouping

NSN 5935-00-660-5914

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mounted
Precious Material And Location:
Contact surafces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0