NSN 5935-00-660-6819

Tip Jack - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-660-6819 |
|--------------------------------------------------------------------------------------------------------------------------------------------|
| Thread Direction: |
| Right-hand |
| Electrical Insulation Feature: |
| Insulated completely |
| Identification Code Color: |
| Black |
| Body Style: |
| Threaded bushing mounted |
| Overall Length: |
| Between 0.922 inches and 1.000 inches |
| Mounting Bushing Length: |
| Between 0.375 inches and 0.438 inches |
| Body Length: |
| 0.500 inches |
| Overall Diameter: |
| 0.312 inches |
| Bushing Accommodation Hole Shape: |
| Round |
| Accommodated Finger Type: |
| Test prod single finger |
| Finger Accommodation Diameter: |
| 0.080 inches single finger |
| Finger Accommodation Length: |
| 0.500 inches single finger |
| Bushing Thru-hole Accommodation Diameter: |
| 0.250 inches |
| Current Rating In Amps: |
| 5.0 |
| Mounting Facility Type And Quantity: |
| 1 bushing |
| Thread Size: |
| 0.250 inches |
| Terminal Type: |
| Tab, solder lug |
| Material: |
| Plastic, polyamide insulator |
| Material: |
| Plastic polyamide insulator |
| Surface Treatment: |
| Any acceptable spring |
| Test Data Document: |
| 81349-milc39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5935-00-660-6819

Tip Jack - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A03400