

View Online at <https://aerobasegroup.com/nsn/5935-00-661-0508>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape w/cable clamp

Overall Diameter:

1.359 inches

Body Angle In Deg:

90.0

Cable Entrance Diameter:

0.531 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sk-c5 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Distance From Centerline To Connector End:

1.438 inches

Distance From Centerline To Cable End:

1.281 inches

Thready Qty Per Inch (tpi):

6

Thread Size:

1.187 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Insert Material Specification:

Mil-m-14, ty cmg military specification single material response single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.005 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.