

View Online at <https://aerobasegroup.com/nsn/5935-00-665-4247>

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

Between 1.922 inches and 2.016 inches

Overall Diameter:

Between 1.797 inches and 1.828 inches

Cable Entrance Diameter:

Between 0.641 inches and 0.672 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nk-27 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

550.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.438 inches

Thready Qty Per Inch (tpi):

6

Thread Size:

1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping or silver single mating end single contact grouping

Insert Material:

Plastic melamine single mating end or plastic phenolic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

27 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold or contact surface silver

Precious Material:

Gold or silver

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0