

View Online at <https://aerobasegroup.com/nsn/5935-00-665-4248>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling w/strain relief

**Overall Length:**

2.000 inches

**Cable Entrance Diameter:**

Between 0.516 inches and 0.547 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Gk-4 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

550.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Length:**

0.454 inches

**Thready Qty Per Inch (tpi):**

6

**Thread Size:**

1.188 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic melamine single mating end or plastic phenolic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.004 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Acme

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0