

NSN 5935-00-665-4251 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-665-4251 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** Between 2.141 inches and 2.235 inches **Overall Diameter:** Between 1.343 inches and 1.375 inches **Cable Entrance Diameter:** Between 0.515 inches and 0.547 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Gk-4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 30.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:**

Cable clamp

Thready Qty Per Inch (tpi):

6

Thread Size:

1.188 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-665-4251Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.004 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0