

View Online at <https://aerobasegroup.com/nsn/5935-00-665-6002>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.715 inches

Overall Diameter:

Between 0.615 inches and 0.635 inches

Environmental Protection:

Hermetic

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

10sl-3 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.438 inches

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping and cadmium single mating end single contact grouping

Insert Material:

Ceramic single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Tin and cadmium

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0