Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-666-0186

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
Between 2.141 inches and 2.235 inches
Overall Diameter:
Between 1.343 inches and 1.375 inches
Cable Entrance Diameter:
Between 0.515 inches and 0.547 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Gk-9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
6
Thread Size:
1.188 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## NSN 5935-00-666-0186 Electrical Plug Connector - Page 2 of 2



	lastic single mating end
	erminal Type:
	older well single mating end single contact grouping
	hell Material:
	luminum alloy
-	hell Surface Treatment:
-	admium
	cluded Contact Quantity:
	single mating end single contact grouping
	ncluded Contact Type:
	ound socket single mating end single contact grouping
	recious Material And Location:
	ontact surfaces gold and contact surfaces silver
	recious Material And Weight:
	.009 gold grains, troy and 0.009 silver grains, troy
-	recious Material:
G	old and silver
Т	hread Series Designator:
U	ns
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
F	iig:
A	039b0