Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-666-1276

| Thread Class: |
|--------------------------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.250 inches |
| Overall Diameter: |
| 0.625 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.703 inches |
| Mounting Facility Thickness: |
| 0.063 inches |
| Threaded Device Type: |
| Coupling facility and mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Uhf single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.375 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| |

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Silver **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material And Weight:** 0.005 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0