NSN 5935-00-666-4874

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-666-4874

Thread Direction: Right-hand Overall Length: 1.190 inches Overall Height: 1.995 inches Overall Width: 1.995 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 132 Thread Size: 0.138 inches <th></th>	
Overall Length: 1.190 inches Overall Height: 1.995 inches Overall Width: 1.995 inches Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Height: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1900.0 all mating ends single contact grouping Contact Maximum Du Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Cocking Method: Latch Thread Sue: 0.138 inches Parater Jourd In Atting ends single contact grouping Contact Maximum Du Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Raximum Cu	Thread Direction:
1.190 inches Verail Height: 1.995 inches Verail Width: 1.995 inches Verail Width: 1.995 inches Environmental Protection: Pressure proof Untreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Holy Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Maximum Current Rating In Amps: Al.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Amps: 1250.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1260.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 127 128 129 129 129 129 129 129 129 129 129 129	-
Overall Heigh: 1.995 inches Overall Width: 1.995 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting Ind Quantity: 2 Contact Removability: Nonremovable all matting ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all matting ends single contact grouping Contact Maximum Current Rating In Volts: 900.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 1250.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 1250.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 1260.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 1260.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Xolts:	Overall Length:
1.995 inches Cverall Width: 1.995 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Height: 1.562 inches Threaded Device Type: Mounting Ind Quantity: 2 Contact Removability: Noremovable all matting ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 900.0 all matting ends single contact grouping Contact Maximum Cu Voltage Rating In Volts: 1250.0 all matting ends single contact grouping Contact Maximum Cu Voltage Rating In Volts: 1250.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Volts: 1250.0 all matting ends single contact grouping Contact Maximum Cu Voltage Rating In Volts: 1260.0 all matting ends single contact grouping Contact Maximum Curvent Rating In Xolts: 1261 <	1.190 inches
Overall Width: 1.995 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nornemovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Curent Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Curolage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Curolage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Curolage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Curolage Rating In Volts: 1250.0 all mating ends single c	Overall Height:
1.995 inches Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Amps: 1250.0 all mating ends single contact grouping Contact Maximum Current Rating In Volts: 1250.0 all mating ends single contact grouping	1.995 inches
Environmental Protection: Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Facilities Plasing endits of the plastic polyamide all mating endits 1900.0 all mating ends Single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Locking Method: 1900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Maximum Current Rating endits	Overall Width:
Pressure proof Unthreaded Mounting Hole Diameter: 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Locking Method: Latch Thready Cty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Insert Material: Plastic polyamide all mating ends Insert Material: Plastic polyamide all mating ends Included Contact Type: Round socket all mating ends single contact grouping Chacked All mating ends single contact grouping Chacked All mating ends Chacked In mating ends Chacked	1.995 inches
Unthreaded Mounting Hole Diameter:0.138 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:1.562 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Width:1.562 inchesThreaded Device Type:Mounting holeMating End Quantiy:2Contact Removability:Nonremovable all mating ends single contact groupingContact Maximum Current Rating In Amps:41.0 all mating ends single contact groupingContact Maximum Ac Voltage Rating In Volts:900.0 all mating ends single contact groupingContact Maximum De Voltage Rating In Volts:1250.0 all mating ends single contact groupingContact Locking Method:1250.1 all mating ends single contact groupingContact Maximum De Voltage Rating In Volts:1250.0 all mating ends single contact groupingContact Locking Method:126127Batienels128Contact Locking Method:129120120121122Contact Locking Method:122123Phread Size:0.138 inchesInsert Material:Plastic polyamide all mating endsIncluded Contact Quantity:138 all mating ends single contact groupingContact All mating ends single contact groupingIncluded Contact Type:Round socket all mating ends single contact groupingContact Contact Type:Round socket all mating ends single contact gro	Environmental Protection:
0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantiy: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Locking Method: Latch Thready Qty Per Inch (tpi): 32 Pinead Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Ingle dots single contact grouping Chulded Contact Quantity: 18 all mating ends single contact grouping Insert Material: Plastic polyamide all mating ends Included Contact Type: Round socket all mating ends single contact grouping	Pressure proof
Center To Center Distance Between Mounting Facilities Parallel To Height: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1901.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1902.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1903.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating ends 1904.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating ends Contact Rating ends single contact grouping Contact Acuantity: 1905.0 all mating ends single contact grouping Contact Contact Type: Round socket all mating ends single contact grouping Contact Series Designator:	Unthreaded Mounting Hole Diameter:
 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contect Locking Method: Latch Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Contact Contact Type: Round socket all mating ends single contact grouping 	0.138 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Pinead Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping	Center To Center Distance Between Mounting Facilities Parallel To Height:
 1.562 inches Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Contact Type: Round socket all mating ends single contact grouping 	1.562 inches
Threaded Device Type: Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Pinread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Mounting hole Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping	1.562 inches
Mating End Quantity: 2 Contact Removability: Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Phread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Cudded Contact Type: Round socket all mating ends single contact grouping	Threaded Device Type:
2 Contact Removability: Norremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Contect Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Contact Gontact Type: Round socket all mating ends single contact grouping	Mounting hole
Contact Removability:Nonremovable all mating ends single contact groupingContact Maximum Current Rating In Amps:41.0 all mating ends single contact groupingContact Maximum Ac Voltage Rating In Volts:900.0 all mating ends single contact groupingContact Maximum Dc Voltage Rating In Volts:1250.0 all mating ends single contact groupingConnector Locking Method:LatchThready Qty Per Inch (tpi):32Nisert Material:Plastic polyamide all mating endsIncluded Contact Quantity:18 all mating ends single contact groupingIncluded Contact Type:Round socket all mating ends single contact grouping	Mating End Quantity:
Nonremovable all mating ends single contact grouping Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping	2
Contact Maximum Current Rating In Amps: 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Size:	Contact Removability:
 41.0 all mating ends single contact grouping Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator: 	Nonremovable all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts: 900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Contact Maximum Current Rating In Amps:
900.0 all mating ends single contact grouping Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	41.0 all mating ends single contact grouping
Contact Maximum Dc Voltage Rating In Volts: 1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Contact Maximum Ac Voltage Rating In Volts:
1250.0 all mating ends single contact grouping Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	900.0 all mating ends single contact grouping
Connector Locking Method: Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Contact Maximum Dc Voltage Rating In Volts:
Latch Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	1250.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Connector Locking Method:
32 Thread Size: 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Latch
Thread Size:0.138 inchesInsert Material:Plastic polyamide all mating endsIncluded Contact Quantity:18 all mating ends single contact groupingIncluded Contact Type:Round socket all mating ends single contact groupingThread Series Designator:	Thready Qty Per Inch (tpi):
 0.138 inches Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator: 	32
Insert Material: Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Thread Size:
Plastic polyamide all mating ends Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	0.138 inches
Included Contact Quantity: 18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Insert Material:
18 all mating ends single contact grouping Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Plastic polyamide all mating ends
Included Contact Type: Round socket all mating ends single contact grouping Thread Series Designator:	Included Contact Quantity:
Round socket all mating ends single contact grouping Thread Series Designator:	18 all mating ends single contact grouping
Thread Series Designator:	Included Contact Type:
-	Round socket all mating ends single contact grouping
Unc	Thread Series Designator:
	Unc

NSN 5935-00-666-4874

Connector Adapter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

