## NSN 5935-00-670-3839

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-670-3839 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 0.990 inches and 1.010 inches **Overall Height:** 0.532 inches **Overall Width:** Between 0.333 inches and 0.353 inches **Distance Between Mounting Facility Centers:** 0.750 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.188 inches Thready Qty Per Inch (tpi): **Thread Size:** 2.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-670-3839

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Quantity: 14 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: C0ntact surfaces gold Precious Material And Weight: 0.014 gold grains, troy Precious Material: Gold Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No Fiig: A039b0